KLS19H

# LCD CONSOLE TRAY, 19", FULL HD

24/7 TECHNICAL SUPPORT AT 877.877.2269 OR VISIT BLACKBOX.COM





# **OVERVIEW**

## LCD CONSOLE TRAY, 19", FULL HD DATA SHEET

### **FEATURES**

- 1U 19" FHD LED-backlit LCD console drawer
- 1920 x 1080 native resolution/16.7M colors
- HDMI 1.4 + VGA video input (speakers excluded)
- 104-key USB keyboard with either touchpad or trackball
- Short depth design of 460mm
- One-man installation design
- Enhanced aesthetics with new molded front panel and 2-point lock
- 2-year standard warranty (upgradable up to 5 years)

#### **OPTIONS**

- Dual stereo speakers for HDMI (HS4.4)
- DP 1.0 + Speakers (DP)
- DVI-D + Audio input & output + Speakers (DV4.4)
- Composite + Audio IN + Speakers (BNC)
- 3G/HD/SD-SDI Broadcast-grade input + Speakers (SDI)
- Front USB hub port for device access (USB)
- DC power: 12V/24V/ 48V/125V/250V
- SUN Micro keyboard option

# **SPECIFICATIONS**

LCD CONSOLE TRAY, 19", FULL HD DATA SHEET

LCD CONSOLE TRAY, 19", FULL HD (KLS19H) SPECIFICATION TABLE								
SPECIFICATION		DESCRIPTION						
CONSOLE PORT								
VIDEO INPUT	HDMI 1.4 + VGA							
KB/MS	USB interface							
VGA CONSOLE 6FT CABLE: KLCBLVGA62 (OPTIONAL) OR	Drawer end: DB-15 + USB type A x 2; Server end: DB-15 + USB type A x 2							
HDMI CONSOLE 6FT CABLE (INCLUDED)	Drawer end: HDMI + USB type A x 2; Server end: HDMI + USB type A x 2							
VIDEO OPTION								
DIGITAL	DVI-D	DVI-D single link						
	DisplayPort™	DP 1.0/HDCP 1.3						
ANALOG	Composite (BNC)	NTSC & PAL						
AUDIO OPTION								
INPUT	Connector: 3.5mm stereo jack; Impedance/Power level: 30kΩ/750mV							
OUTPUT	Connector: 3.5mm stereo jack; Resistance/Power level: 30kΩ/2.8V							
SPEAKER	Dual stereo: 2W x 2							
PHYSICAL								
PRODUCT DIMENSIONS <sup>1</sup> (H X W X D)	Single Console: 1.73"H x 17.4"W x 18.1"D (44 x 442 x 460 mm); Console with KVM: 1.73"H x 17.4"W x 22.8"D (44 x 442 x 580 mm)							
PACKING DIMENSIONS <sup>1</sup> (H X W X D)	Single Console/Console with KVM: 5.5"H x 23.2"W x 31.8"D (140 x 590 x 808 mm)							
NET WEIGHT	Single Console: 25.3 lb. (11.5 kg); Console with KVM: 28 lb. (12.5 kg)							
GROSS WEIGHT	Single Console: 35.2 lb. (16 kg); Console with KVM: 39.8 lb. (18.1 kg)							
MOUNTING DISTANCE	Single Console Drawer: 18.5" ~ 27.6" (470 ~ 700 mm); Console with KVM drawer: 18.5" ~ 31.5" (470 ~ 800 mm)							

All dimensions stated are subject to change if options are selected/integrated to base model part codes.



# **SPECIFICATIONS (CONTINUED)**

LCD CONSOLE TRAY, 19", FULL HD DATA SHEET

LCD CONSOLE TRAY, 19", FULL	L HD (KLS19H) SPECIFICATION TABLE (CONTINUED)
SPECIFICATION	DESCRIPTION
LED-BACKLIT LCD PANEL	
PANEL SIZE (DIAGONAL)	18.5"
NATIVE RESOLUTION	1920 x 1080
BRIGHTNESS (CD/M²)	350
CONTRAST RATIO (TYP.)	1000:1
COLORS	16.7 M
VIEWING ANGLE (L/R/U/D)	89/89/89
RESPONSE TIME (MS)	20
DOT PITCH (MM)	0.213
DISPLAY AREA (MM)	408.98H x 230.04V
SURFACE TREATMENT	Anti-glare, Hard-coating
SURFACE HARDNESS	3H
BACKLIGHT TYPE	LED
MTBF (HRS)	50,000
ENVIRONMENT	
TEMPERATURE	Operating: -4 to 158°F (-20 to +70°C); Storage: -4 to 158°F (-20 to +70°C)
HUMIDITY	Operating: 10 ~ 90%, non-condensing; Storage: 5 ~ 95%, non-condensing
ALTITUDE	Operating: 16,000 ft.; Non-operating: 40,000 ft.
SHOCK	10G acceleration (11ms duration)
VIBRATION	10 ~ 300Hz 0.5G RMS random vibration
POWER	
INPUT	Auto-sensing 100 to 240VAC, 50/60Hz
CONSUMPTION (CONSOLE/KVM)	Screen on: Max. 14W/Max. 45W; Power saving mode: Max. 2W/Max. 34W; Power button off: Max. 1W/Nil
COMPLIANCE	
ЕМС	FCC & CE
SAFETY	CE/LVD & UKCA
ENVIRONMENT	REACH & RoHS3/WEEE
IP CONSOLE	
CONNECTOR	RJ-45
USER MANAGEMENT	1 active user, 15-user login
NETWORK PROTOCOL	DHCP/BOOTP/DNS
SECURITY	TLS 1.3, AES, LDAP, Active Directory (AD), HTTP(s)
BROWSER	Chrome, Firefox, Edge, etc.
RESOLUTION	16:9 - max. 1920 x 1080/16:10 - max. 1920 x 1200/4:3 - max. 1600 x 1200
KEYBOARD	Supporting Layouts: America: US; EMEA: U.K., Germany, France, Russia, Spain, Italy, Switzerland
STANDARD WITH TOUCHPAD	
STANDARD WITH TRACKBALL	

# **ORDERING INFORMATION**

LCD CONSOLE TRAY, 19", FULL HD DATA SHEET

ІТЕМ	CODE
LCD Console Tray, 19", Full HD	KLS19H

KLU17H MODEL WITH KVM									
	IP	REMOTE	8-PORT	12-PORT	16-PORT	32-PORT	CABLES		
2K KVM	0	0	8H2K	_	_	_	KVM Cables:  KLCBLDVD2K6 (6 ft.) DVI-D KVM cable;  KLCBLHDM6 (6 ft.) HDMI KVM cable  Resolution Support:  16:9 - max. 2560 x 1440  16:10 - max. 1920 x 1200  4:3 - max. 1600 x 1200		
DVI-D KVM	0	0	_	12D	_	_	DVI Cables:  KLCBLDV06 (6 ft.);  KLCBLDV15 (15 ft.)  Resolution Support:  16:10 - max. 1920 x 1200  16:9 - max. 1920 x 1080  4:3 - max. 1600 x 1200		
CAT6 MATRIX KVM	1 2 0 0	1 1 1 2 3	- - - -		16CXM3P — 16CX2 —	_ _ _ _	Server Access Modules:  KLCIMUSBC USB-C dongle;  KLCIMDP DP- USB dongle;  KLCIMHDMI HDMI- USB dongle;  KLCIMDV DVI- USB dongle;		
САТ6 СОМВО КУМ	1 O O	O 1 O	8CXC2P 8CXC2 8CXC	_ _ _	16CX2P 16CX2 16CX	— 32CMR 32CM	KLCIMVGA VGA- USB dongle Resolution Support: 16:10 - max. 1920 x 1200 16:9 - max. 1920 x 1080 4:3 - max. 1600 x 1200		
DB-15 COMBO KVM	1 O O	0 1 0	8V2P 8V2 8V		— — 16V	_ _ _	VGA Cables:  KLCBLVGA6 (6 ft.);  KLCBLVGA10 (10 ft.);  KLCBLVGA15 (15 ft.)  Resolution Support:  16:10 - max. 1920 x 1200  16:9 - max. 1920 x 1080  4:3 - max. 1600 x 1200		

#### **ABOUT BLACK BOX**

Black Box® is a trusted IT solutions provider delivering cutting-edge technology solutions and world-class consulting services to businesses on every continent. The breadth of our global reach and depth of expertise accelerate customer success by bringing people, ideas, and technology together to solve real-world business problems. Our IT infrastructure solutions, services, and products enable secure, flawless connectivity and meaningful collaboration across town or around the globe. To learn more, visit the Black Box website at https://www.blackbox.com. Follow the company on Twitter @BlackBox\_ns.

Black Box and the Double Diamond logo are registered trademarks of BB Technologies Inc. All other trademarks referenced herein are the property of their respective owners.

#### **DISCLAIMER**

Black Box Corporation shall not be liable for damages of any kind, including, but not limited to, punitive, consequential or cost of cover damages, resulting from any errors in the product information or specifications set forth in this document and Black Box Corporation may revise this document at any time without notice.

EN\_KVM\_Datasheet\_ KLS19H\_Rev1\_2411.PDF
© COPYRIGHT 2024. BLACK BOX CORPORATION. ALL RIGHTS RESERVED.

